

# WF CA 2

NEW 5 YEAR  
WARRANTY  
ON FLECK CONTROL VALVES

## Carbon Filter

Light Commercial Automatic

Est: 1987



To us it's more than just water...



**Product Description:** Carbon filters are used for water clarification (colour removal), bacterial capture/retention, chlorine removal and odour/taste removal. Carbon must be backwashed regularly to reduce the risk of bio-fouling occurring. Carbon filters don't cope well with sediment loads, it's therefore common to have a mixed bed filter installed prior to handle this.

### Specifications

Type	Automatic Carbon Filter	
Description	Self standing pressure vessel (blue) with top mounted valve	
Media Tank	13" (33cm) x 54" (137cm) wound fibreglass pressure vessel	
Media	28kg of carbon	
Control Valve	Fleck 5000 electronic valve, fast and rapid rinse, full adjustable function, 1-99 day backwash	
Flow Rate	Continuous	35 litres per minute
	Peak	40 litres per minute
Pressure	Maximum	600 kpa (85psi)
	Minimum	175 kpa (25psi)
Pipe Sizes	Inlet/outlet	3/4" (20mm)
	Drain	1/2" (12mm)
Voltage	240 volts with 24 volts step down transformer	

Note: Product specifications are a guide only and can change without notice.



**WA WATER FILTERS**  
HEALTHY WATER HEALTHY LIVING

Water Filters Pty Ltd  
Unit 2, 44 Hutton St, Osborne Park WA 6017  
Telephone 08 6156 0220  
Email: [sales@waterfilter.com.au](mailto:sales@waterfilter.com.au)  
[www.wawaterfilters.com.au](http://www.wawaterfilters.com.au)



**WA WATER FILTERS**  
HEALTHY WATER HEALTHY LIVING