



### Reduction Claim

Sediments	✓
Chlorine	✓
Pesticides & Herbicides	✓
Volatile Organic Compounds	✓
Taste, Odours & Colour	✓
Heavy Metals (Copper, Arsenic, Mercury, Lead...)	✓
Parasites	✓
Bacteria	✓
Viruses	✗

### Replacement Filters Bundle

### SPECIFICATIONS

Dimensions: 270 W x 370 H x 130 D mm  
 Operating Pressure: 200-600 kPa  
 Operating Temperature: 0.6°C - 38°C  
 Flow Rate: 3 LPM

Connection Type: Clip on Hose Connections

### HOSE CONNECTORS

12mm Hose Fittings  
 Have been specifically designed for quick and secure hose to tap connections.



### CHOICE OF FILTERS



With Sediment and Ceramic

**\$284**



With Sediment and Aragon

**\$295**

✓	✓
✓	✓
✓	✓
✓	✓
✓	✓
✓	✓
✓	✓
✓	✓
✓	✓
✗	✓
<b>\$114</b>	<b>\$125</b>

Components are Tested and Certified by NSF International under NSF/ANSI Standard 42 for material requirements only.

To ensure optimal performance and hygiene and to prevent build up of contaminants, we recommend that filters are not used any longer than 12 months. However, replacement frequency also depends on water quality and usage.

A portable water filter designed to connect quickly and easily to your caravan or motor home.

### CONNECTS TO STANDARD GARDEN HOSE FITTINGS

Clip on Hose Caravan Water Filtration Systems are designed to connect easily to garden hose fittings which are readily available in most locations.

### MECHANICAL FILTRATION in the first stage

100% Polypropylene Triple Gradient Sediment Filters are essential in the first stage to capture sand, dirt, rust, algae, silt, mud and particles greater than 1 micron. The sediment filter will avoid premature blockages within the system and will extend the life span of the second stage filter.

### BACTERIOSTATIC FILTRATION TECHNOLOGY in the second stage

The Ceramic Filter and the Aragon Filter in the second stages have silver impregnated. Silver is bacteriostatic, therefore, inhibits bacterial growth inside the filter.

### WATERMARK CERTIFIED SYSTEM AND NSF 42 CERTIFIED COMPONENTS.

Made with materials complying with NSF/ANSI Standard 42.

### CAUTION: To reduce the risk of property damage due to water leakage:

- For Cold water use only. Install on COLD water lines only.
- Never install or operate where inlet water pressure may exceed 120 psi (827kPa)
- Protect from freezing. Remove filter if temperature drop below 1°C.

